

Performance —

PF 600 P BT

PF 600 P TN

Catering

3 - Plastic-coated shelves 530 x 500 mm



Technical data

	PF 600 P TN	PF 600 P BT
Gross volume	511 lt	511 lt
Working temperature	-2+8 °C	-15-22 °C
Motor type	Plug-in	Plug-in
Refrigerant	R290	R290
Refrigeration power	408 W (-10°C / +45°C)	501 W (-25°C / +45°C)
Absorption	343 W	685 W
Voltage/Frequency	230V/1~/50Hz	230V/1~/50Hz

Energy data (UE Reg. 2015/1094)

Climate class	5 / (40°C - 40%)	5 / (40°C - 40%)
Type	This equipment is intended for use in ambient temperatures up to 40°C	

Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit. Equipped with low consumption electronic fan motors	
Refrigerant charge	110 gr	110 gr
Defrost	Automatic by electric heater	
Condensate evaporation	Automatic through anti-corrosion treated compressor coil	

Construction details	PF 600M TN	PF 600M BT
Product dimensions WxDxH	702x675x2060	702x675x2060
Packaging dimensions WxDxH	770x715x2150	770x715x2150
Gross weight	115 Kg	119 Kg
Structure	Stainless steel AISI 304 monocoque	
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel	
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)	
Inner corners	Rounded for an easy cleaning	
Door	1 Self-closing door with 105° door stop. Right hinged, reversible on-site	
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption	
Feet	In AISI 304 stainless steel, height adjustable (90mm-125mm)	

Functions

Control panel	Compact, simple and intuitive touch screen display
Open door alarm	Visual

Accessories

Lock	As standard
No. included accessories	3 - Plastic-coated grid GN 2/1 530x500 mm 3 - Pair of runners for grid 530x500 mm (Mod. 600)

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------

Technical datasheet EN
Performance PF 600 P TN/TB
Updated on 06-04-2024