

Performance —

PF 700 P BT

PF 700 P TN

Catering

3 - Plastic-coated shelves GN 2/1 530 x 650 mm



Technical data	PF 700 P TN	PF 700 P BT
Gross volume	630 lt	630 lt
Working temperature	-2+8 °C	-15-22 °C
Motor type	Plug-in	Plug-in
Refrigerant	R290	R290
Refrigeration power	368 W (-10°C / +45°C)	568 W (-25°C / +45°C)
Absorption	219 W	564 W
Voltage/Frequency	230V/1~/50Hz	230V/1~/50Hz

Energy data (UE Reg. 2015/1094)

Climate class	5 / (40°C - 40%)	5 / (40°C - 40%)
Type	This equipment is intended for use in ambient temperatures up to 40°C	

Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors	
Refrigerant charge	90 gr	115 gr
Evaporator	Cataphoresis-treated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity	
Defrost	Automatic by hot gas for a shorter cycle and less thermal shocks	
Condensate evaporation	Automatic through anti-corrosion treated compressor coil	

Construction details	PF 700 P TN	PF 700 P BT
Product dimensions WxDxH	702x810x2080	702x810x2080
Packaging dimensions WxDxH	770x840x2190	770x840x2190
Gross weight	118 Kg	122 Kg
Structure	Stainless steel AISI 304 monocoque	
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel	
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)	
Inner corners	Rounded for an easy cleaning	
Door	1 Self-closing door with 105° door stop. Right hinged, reversible on-site	
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption	
Feet	In AISI 304 stainless steel, height adjustable (90mm-125mm)	

Functions

Control panel	Compact, simple and intuitive touch screen display
Open door alarm	Visual

Accessories

Lock	As standard
No. included accessories	3 - Plastic-coated grid GN 2/1 530x650 mm 3 - Pair of runners for grid 530x650 mm (Mod. 700/1400)

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------

Technical datasheet EN
Performance PF 700 P TN/TB
Updated on 06-04-2024